

# ICAN 9220 DATASHEET



## PROTECTING AGAINST:

- Harmful dust and other particles
- The maximum level of use is 12 x LV for the particles concerned

## FILTERING FACE MASK – FLAT FOLDED:

Safety mask 9220 is a filtering halfmask for protection against solid- and liquid particles, which meets the demands in the European Standard EN 149:2001+A1:2009, class FFP2 NR.

## TECHNICAL DESCRIPTION:

- ★ The mask is supplied folded.....It will be found comfortable and convenient and contained in a sealed pouch. to keep spare masks to hand
- ★ The mask is made from several layers of filtering material.....High filtering efficiency, soft and comfortable  
Self-extinguishing
- ★ The mask is fitted with an adjustable aluminium noseclip.....Ensures a comfortable, perfect fit.  
with foam at the base of the nose.
- ★ Adjustable cotton head harness.....Easy fitting to shape of the face.  
Elastic that is strong and kind to the skin.
- ★ Weight below 12 grams.....No inconvenience in use – possible to  
Does not restrict speech or vision. communicate without removal of mask.
- ★ Free of maintenance.....Hygienic, no cleaning costs.

## EXAMPLES OF USE:

- |                       |                     |                          |                           |                 |
|-----------------------|---------------------|--------------------------|---------------------------|-----------------|
| ★ ★ Blast cleaning    | ★ Arsenic compounds | ★ Concrete               | ★ Mortar                  | ★ Shale         |
| ★ ★ Building          | ★ Ashes             | ★ Corn dust              | ★ Oil Vapours             | ★ Soap powder   |
| ★ ★ Cleaning/Rinsing  | ★ Brake dust        | ★ Cryolite               | ★ Pesticides              | ★ Stable dust   |
| ★ ★ Farming           | ★ Cellulose         | ★ Enamel particles       | (Powder form, not liquid) | ★ Strychnine    |
| ★ ★ Foundries         | ★ Cement            | ★ Eternit                | ★ Plastic dust            | ★ Sugar         |
| ★ ★ Lagging           | ★ Chalk             | ★ Fibres of mineral wool | ★ Pollen                  | ★ Talcum powder |
| ★ ★ Quarrying         | ★ Chrystobalite     | ★ Flour dust             | ★ Porcelain               | ★ Wood dust     |
| ★ ★ Surface treatment | ★ Coal dust         | ★ Granite                | ★ Quartz                  | ★ Zinc metal    |
|                       | ★ Cocaine           | ★ Marble                 | ★ Quinine                 |                 |
|                       | ★ Colour pigments   | ★ Morphine               | ★ Sandstone               |                 |

(Naturally, it is also possible to use the mask in all fields, where the lower class (FFP1), are used, and thereby obtain greater safety)

## WARNING!

The mask does not protect against:

Oxygen deficiency (The content of oxygen in the air must not fall below 19%). Gases and dangerous vapours, radioactive dust, bacteria, virus and some carcinogenic substances. Persons with a beard or facial hair intervening between the face and the mask cannot expect to receive effective protection and instead should consider using ICAN TURBO UNIT.

ICAN 9220 is a safety mask which is widely used from our range.

ICAN 9220 is approved in accordance with the European Standard EN 149:2001+A1:2009, and is marked with CE.

ICAN 9220 has been thoroughly tested by a number of users in different working situations, where safety masks are obligatory or improves the environment, and the safety of the user. If the work is physically demanding, and / or hot, a mask with exhalation valve, for example ICAN 9225, should be used.